

THERMOCOUPLE THERMOMETERS (RECORD TYPE)





- Unit: °C/°F
- Support thermocouple type K/J/T
- MAX/MIN/AVG mode
- 20000 data storage
- Graphical display
- Display backlight
- Multi-point calibration function
- Temperature upper and lower limit alarm function
- Data hold function
- Battery level display
- Automatic power off
- Computer software is included



0327-DL32

SPECIFICATION

Code		0327-DL31	0327 - DL32
Channel number		1	2
Weight		233g	248g
Thermocouple type		K/J/T	
Temperature range	type K	-200°C~1370°C	
	type J	-200°C~1200°C	
	type T	-200°C~400°C	
Temperature accuracy		±(0.3%· t +0.40)°C	
Temperature resolution		0.01°C	
Sampling rate		2 times/sec	
Logging interval		1s~86399s (adjustable)	
Memory capacity		20000	
Data transmission		Micro USB	
Display		dot matrix LCD display with backlight	
Operation temperature		-10°C~+50°C (non-condensing)	
Storage temperature		-20°C~+60°C (without battery)	
Power supply		3×AAA alkaline batteries	
Dimension		174×73×40mm	

^{*}Temperature accuracy does not include thermocouple error

STANDARD DELIVERY

0.7.0.127.0.12 2221.1.1.1		
Main unit	1 pc	
Battery (AAA)	3 pcs	
USB cable	1 pc	
K-type thermocouple (0326-K01)*	1/2 pcs	

^{*}Number of thermocouples is corresponding to the number of channels

SPECIFICATION OF K-TYPE THERMOCOUPLE*

Code	Range	Accuracy	Length
0326-K01	-40°C~300°C	±1.5°C	1.5m

^{*}Other types, temperature range and length of thermocouples can be customized

computer software (included): connect to PC software via USB cable to collect, display and store data, and can be saved as TXT/CSV/XLS/PDF formats

