

EDDY CURRENT CONDUCTIVITY TESTER

CODE 0420-EL60

DATA
OUTPUT

INSPECTION
CERTIFICATE



VIDEO

- Measure conductivity (MS/m, %IACS) and resistivity ($\Omega \cdot \text{mm}^2/\text{m}$) of non-ferromagnetic metals or alloys with eddy current phase detection
- With temperature compensation, even when the temperature of the calibration block and the material are different, test results can be automatically compensated
- Lift-off compensation function ensures accurate results when there are non-conductive layers such as coatings, dust, rough surfaces, etc., and reduces measurement error caused by operation as well
- Measure with high speed and efficiency, results show on screen after probe touch with the material in 1 second
- Data can be saved manually or automatically and exported to Excel with computer software
- Wear-resistant and heat-resistant probe
- Unit switch
- Display with backlight
- Language: English, Chinese, Japanese



SPECIFICATION

Conductivity	range	0.3MS/m~65MS/m or 0.51%IACS~112%IACS
	unit	MS/m, %IACS
	resolution	0.01 (<30MS/m or <30%IACS) 0.1 (30MS/m~65MS/m or 30%IACS~112%IACS)
	accuracy *	20°C: ±0.5%: 4.00MS/m~65.0MS/m or 6.90%IACS~112.0%IACS 0°C~40°C: ±(1.0%+1d): 0.30MS/m~4.00MS/m ±(1.0%+2d): 0.51%IACS~6.90%IACS ±1.0%: 4.00MS/m~65.0MS/m or 6.90%IACS~112.0%IACS
Resistivity	range	0.01538 $\Omega \cdot \text{mm}^2/\text{m}$ ~3.3333 $\Omega \cdot \text{mm}^2/\text{m}$
	unit	$\Omega \cdot \text{mm}^2/\text{m}$
	resolution	0.00001 (<1.0000 $\Omega \cdot \text{mm}^2/\text{m}$) 0.0001 (1.0000~3.3333 $\Omega \cdot \text{mm}^2/\text{m}$)
Temperature	range	0°C~50°C
	resolution	0.1°C
	accuracy	±1.0°C
Test frequency		60kHz sinewave
Probe diameter		Ø14mm
Lift-off compensation		maximum 500 μm
Storage capacity		16000 groups
Interface		USB, RS232 protocol
Calibration block		about 0.60MS/m, 4.10MS/m, 58.0MS/m refer to values marked on the supplied blocks
Operation environment		temperature: 5°C~45°C humidity: <95%RH, no condensation
Power supply		3.7V rechargeable Li-ion battery
Dimension		230×97×60mm
Weight		370g

* d is resolution

STANDARD DELIVERY

Main unit	1 pc
Probe (0420-TP01)	1 pc
Calibration block (0420-CB01)	3 pcs
USB cable	1 pc
AC/DC adapter	1 pc



calibration blocks
(included)



USB cable (included)