

VIBRATION ISOLATION PLATFORMS (BASIC TYPE)

CUSTOMIZABLE

- Suitable for equipment with low vibration requirement
- Stable and reliable in structure, convenient to install, and requiring little post-maintenance
- Effectively reduce the vibration energy in medium-high frequency ranges, and effectively isolate external vibration disturbances
- Vibration isolation support adopts rubber vibration damper



rubber vibration damper
(included)

0790-B129B

STANDARD DELIVERY

Main unit	1 pc
Rubber vibration damper	4 pcs

SPECIFICATION

Code	0790-B88A	0790-B88B	0790-B108A	0790-B108B	0790-B129A	0790-B129B
Countertop material	marble	honeycomb platen	marble	honeycomb platen	marble	honeycomb platen
Threaded hole/pitch	—	M6/25×25mm	—	M6/25×25mm	—	M6/25×25mm
Countertop thickness	100mm		100mm		100mm	
Max. load	400kg		400kg		600kg	
Foot	foot cup+caster		foot cup+caster		foot cup+caster	
Dimension (L×W×H)	800×800×800mm		1000×800×800mm		1200×900×800mm	
Weight	260kg	160kg	330kg	230kg	350kg	250kg

SPECIFICATION

Code	0790-B159A	0790-B159B	0790-B1812A	0790-B1812B	0790-B2012A	0790-B2012B
Countertop material	marble	honeycomb platen	marble	honeycomb platen	marble	honeycomb platen
Threaded hole/pitch	—	M6/25×25mm	—	M6/25×25mm	—	M6/25×25mm
Countertop thickness	200mm		200mm		200mm	
Max. load	600kg		800kg		800kg	
Foot	foot cup+caster		foot cup+caster		foot cup+caster	
Dimension (L×W×H)	1500×900×800mm		1800×1200×800mm		2000×1200×800mm	
Weight	750kg	600kg	800kg	650kg	850kg	700kg

Natural frequency	vertical: 5Hz~10Hz horizontal: 4Hz~8Hz	
Vibration isolation mode	rubber vibration damper	
Leveling mode	manual leveling	
Height adjustment	±20mm	
Platform height	800mm	
Countertop flatness	marble: grade 00 (DIN 876) honeycomb platen: 0.05mm/m ² ~0.1mm/m ²	