## INTERCHANGEABLE HEAD TORQUE WRENCHES








- According to DIN ISO 6789, ASME B107.300
- Dual window design with clear scale
- Non-slip grip handle
- Push-pull locking device, easy to operate

#### **SPECIFICATION**

Code	Range (clockwise)	Accuracy	Graduation	Socket Size (A×B)	Length	Weight
IST-29WM25	5~25N.m	±3%	0.2N.m	12×9mm	315mm	700g
IST-29WM50	10~50N.m	±3%	0.5N.m	12×9mm	376mm	820g
IST-29WM60	10~60N.m	±3%	0.5N.m	12×9mm	376mm	820g
IST-29WM100	20~100N.m	±3%	0.5N.m	12×9mm	417mm	900g
IST-29WM150	30~150N.m	±3%	1N.m	18×14mm	460mm	1150g
IST-29WM200	40~200N.m	±3%	1N.m	18×14mm	478mm	1200g
IST-29WM300	60~300N.m	±3%	1.5N.m	18×14mm	538mm	1200g
IST-29WM400	80~400N.m	±3%	2N.m	18×14mm	694mm	1600g
IST-29WM550	100~550N.m	±3% (≤500N.m) ±4% (>500N.m)	3N.m	32×24mm	919mm	2000g
IST-29WM750	150~750N.m	±3% (≤500N.m) ±4% (>500N.m)	5N.m	32×24mm	1070mm	4000g
IST-29WM850	200~850N.m	±3% (≤500N.m) ±4% (>500N.m)	5N.m	32×24mm	1137mm	4200g

# torque correction





### RATCHET HEAD (optional)

Code	Square driver	Applicable wrenches
IST-11WM-R1	1/4"	IST-29WM25
IST-11WM-R2	3/8"	IST-29WM25, IST-29WM50, IST-29WM60, IST-29WM100
IST-11WM-R3	1/2"	IST-29WM150, IST-29WM200, IST-29WM300, IST-29WM400
IST-11WM-R4	3/4"	IST-29WM150, IST-29WM200, IST-29WM300, IST-29WM400
IST-11WM-R5	3/4"	IST-29WM550, IST-29WM750, IST-29WM850





### OPEN END HEAD (optional)

Code	Open size	Applicable wrenches
IST-11WM-K8	8mm	
IST-11WM-K10	10mm	IOT COMMISSE
IST-11WM-K13	13mm	IST-29WM25 IST-29WM50
IST-11WM-K14	14mm	IST-29WM60
IST-11WM-K15	15mm	IST-29WM100
IST-11WM-K17	17mm	
IST-11WM-K19*	19mm	
IST-11WM-K13A	13mm	
IST-11WM-K14A	14mm	
IST-11WM-K15A	15mm	
IST-11WM-K17A	17mm	IST-29WM150
IST-11WM-K19A	19mm	IST-29WM200
IST-11WM-K22A	22mm	IST-29WM300
IST-11WM-K24A	24mm	IST-29WM400
IST-11WM-K27A*	27mm	
IST-11WM-K30A*	30mm	
IST-11WM-K32A*	32mm	
IST-11WM-K22B	22mm	
IST-11WM-K24B	24mm	
IST-11WM-K27B	27mm	
IST-11WM-K28B	28mm	IST-29WM550
IST-11WM-K30B	30mm	IST-29WM750
IST-11WM-K32B	32mm	IST-29WM850
IST-11WM-K33B*	33mm	
IST-11WM-K36B*	36mm	
IST-11WM-K38B*	38mm	
IST-11WM-K40B*	40mm	

### **BOX END HEAD (optional)**

Code	Open size	Applicable wrenches
IST-11WM-M8	8mm	
IST-11WM-M10	10mm	IOT COMMISS
IST-11WM-M13	13mm	IST-29WM25 IST-29WM50
IST-11WM-M14	14mm	IST-29WM60
IST-11WM-M15	15mm	IST-29WM100
IST-11WM-M17	17mm	
IST-11WM-M19	19mm	
IST-11WM-M13A	13mm	
IST-11WM-M14A	14mm	
IST-11WM-M15A	15mm	
IST-11WM-M17A	17mm	IST-29WM150
IST-11WM-M19A	19mm	IST-29WM200
IST-11WM-M22A	22mm	IST-29WM300
IST-11WM-M24A	24mm	IST-29WM400
IST-11WM-M27A*	27mm	
IST-11WM-M30A*	30mm	
IST-11WM-M32A*	32mm	
IST-11WM-M22B	22mm	
IST-11WM-M24B	24mm	
IST-11WM-K27B	27mm	
IST-11WM-M28B	28mm	IST-29WM550
IST-11WM-M30B	30mm	IST-29WM750
IST-11WM-M32B	32mm	IST-29WM850
IST-11WM-M33B	33mm	
IST-11WM-M36B*	36mm	
IST-11WM-M38B*	38mm	
IST-11WM-M40B*	40mm	



type C (optional)



type UM (optional)



type M (optional)



type O (optional)



type A (optional)

#### **ER WRENCH HEAD (optional)**

ER WILLIAM (optional)		
Type C*		
Type UM*	Overtouries descending to	
Type M*	Customized according to customer requirements	
Type O*		
Type A*		

<sup>\*</sup> Torque value needs to be corrected for these heads