

SINGLE-ELEMENT STRAIGHT PROBES

CUSTOMIZABLE

- Suitable for detecting defects on parallel surfaces or near-parallel surfaces
- Made of metal, sturdy, good shielding performance
- Vertical incident longitudinal wave detection by direct probe contact with the workpiece surface
- The contact surface is made of hard wear-resistant material, which matches well with the metal acoustic impedance, high sensitivity and strong penetration



Code explanation:



Code example:

UFD-S6D1F1	S6-frequency 5.0MHz
	D1-element size Ø6mm
	F1-interface type C6

Optional probe connector plug type



SPECIFICATION (WITHOUT SOFT FILM PROBE)

Frequency	Element size Casing dimension	Interface type
5.0MHz (S6)	Ø6mm (D1)	C6 (F1)
7.5MHz (S7)	12×25×10mm	
10.0MHz (S8)		
2.5MHz (S4)	Ø8mm (D2)	
5.0MHz (S6)	15×28×11mm	
7.5MHz (S7)		
10.0MHz (S8)		
2.5MHz (S4)	Ø10mm (D3)	
5.0MHz (S6)	16×28×13mm	
7.5MHz (S7)		
10.0MHz (S8)		
0.5MHz (S1)	Ø12mm (D4)	Q9 (F2)
1.0MHz (S2)	20×39×16mm	
2.5MHz (S4)		
5.0MHz (S6)		
1.0MHz (S2)	Ø14mm (D5)	
2.5MHz (S4)	24×31×17mm	
5.0MHz (S6)		
0.5MHz (S1)	Ø20mm (D6)	
1.0MHz (S2)	30×32×23mm	
2.5MHz (S4)		
5.0MHz (S6)		
0.5MHz (S1)	Ø30mm (D7)	
1.0MHz (S2)	42×40×34mm	
2.5MHz (S4)		

SPECIFICATION (WITH SOFT FILM PROBE)

Frequency	Element size Casing dimension	Interface type
2.0MHz (S3)	Ø10mm (D9)	C5 (F3)
4.0MHz (S5)	25×47×13mm	
5.0MHz (S6)		
0.5MHz (S1)		
1.0MHz (S2)	Ø20mm (D10)	C9 (F4)
2.0MHz (S3)	35×50×23mm	
4.0MHz (S5)		
0.5MHz (S1)	Ø24mm (D11)	
1.0MHz (S2)	44×56×30mm	
2.0MHz (S3)		
4.0MHz (S5)		
0.5MHz (S1)	Ø30mm (D12)	
1.0MHz (S2)	50×57×33mm	
2.0MHz (S3)		
4.0MHz (S5)		

STANDARD DELIVERY

Probe	1pc
-------	-----

OPTIONAL PROBE WIRE

Code	Probe connector plug type
UFD-PC01	Q9-Q9
UFD-PC02	C5-Q9
UFD-PC03	C6-Q9
UFD-PC04	C9-Q9